



20844 Harper Avenue, Suite 300
 Harper Woods, MI 48225
 Phone: 513-576-0123
 www.milairinc.com

Environmental Control System Model ECS-20T (147)

Performance

Cooling Capacity: 20,000Btu/h (5.9 kW)	Total Heating Capacity: 20,478 Btu/hr (6.0 kW)
Design Ambient Cooling: 122°F (50°C)	Minimum Ambient Heating: -40°F (-40°C)
Minimum Ambient Cooling: 50° F (10°C)	Supply Air Flow Rate: 800 CFM (22.7 CMM)
Design Return Air Temperature: 90° F (32.2°C) db	Evaporator Static Pressure: .25 Inch Water

Characteristics

Refrigerant: R407c	Size (L x W x H): 30.00" x 33.00" x 20.00"
Compressor: Hermetic Scroll Type	76.2 cm x 83.8 cm x 50.8 cm
Evaporator Coil: Alum. Fin/Copper Tube	Frame & Panels: Aluminum
Condenser Coil: Alum. Micro-Channel	Weight: 250 lbs. (113.4 kg)
Circulating Fan: Motorized Impeller	Remote Control Panel: Cool/Vent/Off/Heat
Condenser Fan: Propeller	Thermostat Temp Control
	Fault Indicator

Electrical

Input Voltage: 240 VAC	Max Power Consumption: 6.5 kW (Heat)
Number of Phases: 1Φ	Wires: 4-Wire
Frequency: 60 Hz	Control Power: 120 VAC - 1Φ - 60 Hz

Standard Features

- Sealed Motors
- Refrigerant Access Valves
- Remote Control Cable (30 ft.)
- Retractable Lift Handles (4)
- Supply/Return Flex Ducts, 10" Dia. x 6 ft. long
- Washable Metal Return Filter
- Refrigerant Sight Glass

Specification Compliance

- ASHRAE 34 Designation and Classification of Refrigerant
- ASHRAE 37 Testing for Rating Unitary Air Conditioning
- MIL-DTL-53072 Chemical Agent Resistant Coating System
- MIL-F-14072 Finishes for Ground Based Electronic Equip.
- MIL-HDBK-1791 Design for Internal Aerial Delivery
- MIL-STD-130K Identification Marking of Military Prop.
- MIL-STD-461E Control of Electromagnetic Interference
- MIL-STD-810F (Air, Land, Rail and Sea Transportation)
- NFPA 70 National Electric Code

Options

- Finish to Specification
- Remote Backdraft Damper for N+1 Configuration
- Power Cable
- Four-Wheeled Transport Cart
- Coil Corrosion Protection (MIL-DTL-5541 Conversion Coating, Heresite, or Electrofin)
- N+1 Remote Controller
- Fresh Air Intake

Please contact sales@milairinc.com for additional options and interface control drawing