



20844 Harper Avenue, Suite 300
 Harper Woods, MI 48225
 Phone: 513-576-0123
 www.milairinc.com

Environmental Control System Model ECS-24H (1058)

Performance

Cooling Capacity (50 Hz):	22,000 Btu/h (6.4 kW)	Total Heating Capacity	13,649 Btu/hr (4.0 kW)
Cooling Capacity (60 Hz):	24,500 Btu/h (7.2 kW)	Minimum Ambient Heating:	-4°F (-20°C)
Design Ambient Cooling:	131°F (55°C)	Supply Air Flow Rate:	800 CFM (22.7 CMM)
Minimum Ambient Cooling:	40°F (4.4°C)	Evaporator Static Pressure:	.75 Inch Water
Design Return Air Temperature:	88°F (31.1°C) db	Fresh Air Flow Rate:	40 CFM (1.13 CMM)

Characteristics

Refrigerant	R407c	Condenser Fan:	Propeller
Compressor	Hermetic Scroll Type	Size (L x W x H):	36.00" x 40.00" x 22.06"
Evaporator Coil:	Alum. Fin/Copper Tube		91.5 cm x 101.6 cm x 56.0 cm
Condenser Coil:	Alum. Micro-Channel	Weight:	365 lbs. (165.6 kg)
Circulating Fan:	Motorized Centrifugal	Remote Control Panel:	Cool/ Vent/Off/Heat Thermostat Temp Control

Electrical

Input Voltage:	230 VAC	Max Power Draw:	5.0 kW (50 Hz)
Number of Phases:	1Φ	Wires:	3-Wire
Frequency:	50/60 Hz	Control Power:	120 VAC

Standard Features

- Sealed Motors
- Washable Metal Return Air Filter
- Refrigerant Access Valves
- Refrigerant Sight Glass
- Hot Gas Bypass (HGB)
- All Aluminum Construction
- Transit Cover

Specification Compliance

- ASHRAE 34 Designation and Classification of Refrigerant
- ASHRAE 37 Testing for Rating Unitary Air Conditioning
- MIL-DTL-53072 Chemical Agent Resistant Coating System
- MIL-F-14072 Finishes for Ground Based Electronic Equip.
- MIL-HDBK-1791 Design for Internal Aerial Delivery
- MIL-STD-130K Identification Marking of Military Prop.
- MIL-STD-461E Control of Electromagnetic Interference
- MIL-STD-810F (Air, Land, Rail and Sea Transportation)
- NFPA 70 National Electric Code

Options

- Finish to Specification
- Hour Meter
- Coil Corrosion Protection (MIL-DTL-5541 Conversion Coating, Heresite, or Electrofin)

Please contact sales@milairinc.com for additional options and interface control drawing