



20844 Harper Avenue, Suite 300  
 Harper Woods, MI 48225  
 Phone: 513-576-0123  
 www.milairinc.com

## Environmental Control System Model ECS-60V (192B)

### Performance

Cooling Capacity: 57,300 Btu/h (16.8 kW) Design Ambient Cooling: 122°F (50°C) Minimum Ambient Cooling: 40° F (4.4°C) Design Return Air Temperature: 95°F (35°C) db	Total Heating Capacity: 64,000 Btu/hr (18.8 kW) Minimum Ambient Heating: -40°F (-40°C) Supply Air Flow Rate: 2000 CFM (56.6 CMM) GPFU Air Flow Rate: 400 CFM (11.3 CMM)
---	--

### Characteristics

Refrigerant: HFC-134a Compressor: Hermetic Scroll Type Evaporator Coil: Alum. Fin/Copper Tube Condenser Coil: Alum. Micro-Channel Circulating Fan: Centrifugal Condenser Fan: Propeller	Size (L x W x H): 45.0" x 48.0" x 96.0" 114.3 cm x 121.9 cm x 243.8 cm Frame & Panels: Aluminum Weight: 1,223 lbs. (554.7 kg) Remote Control Panel: Cool/Vent/Off/Heat Thermostat Temp Control GPFU Control
--	---

### Electrical

Input Voltage: 480 VAC Number of Phases: 3Φ Frequency: 60 Hz	Max Power Draw: 25.9 kW (Heat) Wires: 4-Wire Control Power: 24 VAC – 1Φ– 60 Hz
--	--

### Standard Features

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Sealed Motors</li> <li>• Gas Particulate Filter Unit (GPFU)</li> <li>• Insulated Evaporator Cabinet</li> <li>• Refrigerant Access Valves</li> <li>• Hour Meter</li> </ul> | <ul style="list-style-type: none"> <li>• Refrigerant Sight Glass</li> <li>• Hot Gas Bypass (HGB)</li> <li>• Fork Pockets</li> <li>• Lift Rings</li> <li>• Bottom ISO Twistloc Aperture Plates</li> </ul> |
|--|--|

### Specification Compliance

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• ASHRAE 34 Designation and Classification of Refrigerant</li> <li>• ASHRAE 37 Testing for Rating Unitary Air Conditioning</li> <li>• MIL-DTL-53072 Chemical Agent Resistant Coating System</li> <li>• MIL-F-14072 Finishes for Ground Based Electronic Equip.</li> <li>• MIL-HDBK-1791 Design for Internal Aerial Delivery</li> </ul> | <ul style="list-style-type: none"> <li>• MIL-STD-130K Identification Marking of Military Prop.</li> <li>• MIL-STD-461E Control of Electromagnetic Interference</li> <li>• MIL-STD-810F (Air, Land, Rail and Sea Transportation)</li> <li>• NFPA 70 National Electric Code</li> </ul> |
|---|--|

### Options

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• Finish to Specification</li> <li>• Control Unit to Specification</li> <li>• Phase Monitor</li> </ul> | <ul style="list-style-type: none"> <li>• Coil Corrosion Protection (MIL-DTL-5541 Conversion Coating, Heresite, or Electrofin)</li> </ul> |
|---|--|

Please contact [sales@milairinc.com](mailto:sales@milairinc.com) for additional options and interface control drawing